

EP2000TE-VG/LS

Article nr.: 987002003



Generator :

	<u>3~ 400V</u>	<u>1~ 230V</u>
Standby output (kVA):	20	6,6
Standby output (kW):	16	6,6
Cont. output (kVA):	18	6
Cont. output (kW):	14,4	6
Amps (continuous):	21	26
Dimensions in cm (l x w x h):	100 x 64 x 72	
Dry weight (kg):	210	

Engine:

Brand / Type:

BRIGGS & STRATTON VANGUARD 31HP

Power:	23 kW (3600 rpm), gasoline, 2-cylinder, air-cooled	
Displacement:	895 cm ³	
Consumption (at 75% load):	7 litres/hour	
Tank:	41 litres	
Autonomy (at 75% load):	5,8 hours	
Starter:	Electric (12V)	
Noise level at 75% load at 7m:	79 dB(A)/7m	
Equipment:	with oil pressure security	

Alternator:

Brand / Type:

Leroy Somer LSA 37M8, 18kVA - AVR - brushless

Nominal voltage:	3~ 400V + 1~ 230V	
Frequency:	50 Hz (3000 rpm)	



Your **EUROPOWER** distributor

Arguments:

- Generating set with high quality VANGUARD 31HP gasoline engine, 2-cylinder, air-cooled
- Brushless Leroy Somer alternator LSA37M8 with AVR (+/- 1% voltage accuracy)
- Protection covers
- Central built-in lifting eye
- Fuel pump (type membrane pump)
- Large integrated tank with mechanical fuel level meter
- Control panel with:
 - voltmeter
 - hour counter
 - sockets (1 x schuko 230V, 1 x 16A 230V 3-poles CEE, 1 x 32A 400V 5-poles CEE)
 - thermal-magnetic protections
- Maintenance: fuel filter, oil filter, air cleaner element, oil filler cap, oil/fuel drain are easily accessible
- Battery 12V 45Ah

Options:

- Earth leakage protection + earth pin
- Insulation protection "IB Protector" combined with over voltage, under voltage and frequency protection, with user code
- Amp. meters, frequency meter
- Automatic Start Stop System in case of mains failure
- Remote control
- Wheel kit
- Star-delta switch

